Moisture Analyzer

MA100C Moisture Analyzer

Fully Automatic Infrared Moisture Analyzer with Ceramic Heating Element



- Time-saving and convenient alternative to a drying oven
- Comprehensive range of options for flexible adaptation to various drying tasks
- Ideally suited for ambitious measuring tasks in the fields of quality control or research
- Utmost safety due to self-calibrating system and full GMP suitability
- Particularly well suited for samples with demanding drying behaviour and very dry samples

Max. weighing capacity	100 g
Repeatability, typical	Starting at an initial sample weight of approx. 1 g: ± 0.1% | starting at an initial sample weight of approx. 5 g: ± 0.02%
Readability	1 mg, 0.01% | 0.1 mg, 0.001%
Typical sample quantity	5 – 15 g
Reading display	% moisture content (optionally available with conversion factor) | % dry weight | RATIO value | mg weight loss | g residue | g/kg residue | g/l residue
Temperature range and settings	30°C–180°C, stand-by temperature selectable from 30–100°C in increments of 1 degree
Sample heating	Infrared heating using a round ceramic heating element
Heating programs	Standard, quick, gentle and phase drying
Shutoff criteria	Optional: – Fully automatic – SPRM mode (optimization to a reference system) – Semi-automatic (1–50 mg/5–300 sec.) – Semi-automatic (0.1-5.0%/5–300 sec.) – Timer setting (3× 0.1–999 min.) – Timer setting + fully/semi-automatic (2× 0.1–999 min. + automatic) – Manual
Access to sample chamber	Motorized cover
Measuring program	30 programs saved in a non-volatile memory (freely selectable parameters)
Data storage	Result statistics for the last 9999 measurements/program
Operator guidance features	Menu-driven, alphanumeric dialogue text (5 languages selectable)
Parameter | data entry	– Optimized text entry via softkeys – Numeric entry via keypad – Optional data entry via barcode scanner
Report printout	– Printout using the optional, internal printer YDP01MA – Configurable GLP-report for measuring results | calibration | adjustment (5 languages selectable)



Easy to clean



With optional printer YDP01MA

Test equipment monitoring	– Internal calibration weight – Automatic reproTEST for the weighing system – Automatic temperature calibration with optional temperature adjustment set YTM03MA – Documentation in accordance with the applicable quality assurance requirements
Safety	Parameter settings password-protected against unauthorized access
Voltage frequency	48-60 Hz
Power consumption	Max. 700 VA
Operating temperature range	10°C...30°C
Housing dimensions (W × D × H)	350 × 453 × 156
Weight	Approx. 8.0 kg

Available Models

	Supply voltage
MA100C-000115V1	115 V +15%, –20%
MA100C-000230V1	230 V +15%, –20%

Accessories

6965542	Disposable sample pans, 80 units, aluminum, round, ∅ 90 mm
6906940	Fiberglass pad, ∅ 90 mm for pasty and fatty samples, hard quality, 80 units
6906941	Fiberglass pad, ∅ 90 mm for liquid and fatty samples, soft quality, with high suction force, 200 units
YAT01MA	Single-use pipettes for weighing liquid samples, 500 units
YDS03MA	Panel replacement set, aluminum panels for replacing glass panels, to meet FDA|HACCP regulations (conversion kit)
YSC02	SartoCollect, software for data communication between moisture analyzer and PC (connecting cable must be ordered separately) Prerequisite: MS Windows 2000 | Windows XP Professional, Vista Ultimate, Windows 7 Ultimate.
YCW4528-02	External calibration weight, 50 g (E2) with DKD certificate
YTM03MA	Temperature adjustment set with manufacturer certificate for adjustment of the heat source
YDP01MA	Data printer, suitable for integration
YDP20-0CE	Data printer, suitable for external verification, with date, time, statistics, numerator including cable
6906918	Ink ribbon for data printer
6906937	Paper rolls for data printer, 5 rolls, 50 m each

Equipment Supplied

– Moisture analyzer with data interface
– Power cord
– User manual
– 80 alu sample pans
– In-use dust cover for keypad
– 1 pair of forceps
– Laminated short-form manual (6 languages)

salmenkipp
T 0346 26 90 90
F 0346 26 48 14
I www.salmenkipp.nl
E info@salm-en-kipp.nl