DASITGROUP FAST ER

CHEMFAST ELITE

TECHNICAL DATASHEET



MADE IN ITALY

TECHNICAL SPECIFICATIONS

FUME CUPBOARD

FASTER ChemFAST Elite | according to NFX15-211

Description	Unit	0,6 m	0,9 m	1,2 m	1,5 m	1,8 m
Type				CAV		
General dimensions W×H×D	mm	595×1120×760	885×1120×760	1185×1120×760	1500×1120×760	1800×1120×760
Usable dimensions W×H×D	mm	553×660×600	823×660×600	1123×660×600	1438×660×600	1738×660×600
Work surface	mm	PVC	PVC	PVC	Stainless steel	Stainless steel
Unit height with base frame (Standard)	mm			1920		
Working height (seated workstation)	mm			810		
Working opening	mm			200		
Max. front opening	mm			455		
Weight	kg	70	85	100	120	135
Exhaust air	m³/h	300	400	600	700	800
Prefilter (particulate)		1	2	2	3	4
Inflow	m/s			>0,6		
Noise level	dB(A)			<57		
Light intensity	lux			>1000		
Electrical connection				1 Ph+E - 230 V 50 Hz, cable lenght 2,5 m (SchuKo plug)		
Power consumption	W	88	122	207	210	279
Protection class / IP				1 / 20		
Internal fuse protection	A			4		
Sockets IP66			○	○	○	○
The following filter types are available (unit):		Optional: With 2nd filtration level two filters can be combined. ▪ AC Filter ▪ ACR Filter ▪ AM Filter		▪ CYAN Filter ▪ FORM Filter ▪ HEPA Filter		▪ MER Filter ▪ SULF Filter ▪ UR Filter
Exhaust air spigot diameter	mm			200		
Underframe		○	○	○	○	○
Display				Multifunction display		
Gas detector		●	●	●	●	●

● Standard ○ Optional

DASITGROUP FAST ER

EN/Tec_ChemFAST-Elite EN/2026-04/Ed. 03 In this brochure all pictures and specifications are purely indicative and may vary without notice.